



Cisco Multiplatform 8800 IP Phone Key Expansion Module

Quickly adapt to market changes. Increase productivity. Improve competitive advantage through speed and innovation. And deliver a rich-media experience across any workspace securely and with the best possible quality. Cisco® Unified Communications Solutions enable the collaboration that makes this possible (Figure 1).



Figure 1. Cisco MP IP Phone 8800 Key Expansion Module

Product Overview

Call coverage is critical for administrative assistants and others who must monitor and manage the status of calls. It requires the ability to instantly determine the status of numerous lines beyond those of the Cisco MP IP Phone 8851, 8861, and 8865 models.

The Cisco MP IP Phone 8800 Key Expansion Module (KEM) extends the capabilities of Cisco MP IP Phone 8851, 8861, and 8865 models with additional buttons and a color LCD display. This key expansion module adds 18 physical keys with access to 18 additional keys, using the page keys, for a total of 36 additional keys.

- Cisco MP 8861 and 8865 IP Phones can support up to three 8800 KEMs
- Cisco MP 8851 IP Phone can support up to two 8800 KEMs

The 8800 KEM comes with a foot stand and all necessary hardware to connect it directly to the base device in the traditional side-by-side fashion.



Cisco Multiplatform 8800 IP Phone Key Expansion Module

Features and Benefits

The large LCD display of the Cisco MP IP Phone 8800 Key Expansion Module allows for quick and easy identification of associated buttons. Using the settings menu of the IP Phone 8851, 8861, and 8865 models, you can adjust the brightness of the individual KEM LCD according to your preference.

The primary function of the 8800 KEM is to provide additional keys for directory numbers, speed dial, or programmable feature keys to the IP Phone 8851, 8861, and 8865 models. These keys are illuminated, and when configured as directory numbers or shared-line keys they allow for easy identification of line status. The 8800 KEM is an ideal call-coverage tool. It provides features that are similar, but not intended to be directly comparable to those of traditional direct station selection/busy lamp field (DSS/BLF) modules; therefore, it is neither an operator nor an attendant console.

The two illuminated page buttons below the Cisco MP IP Phone 8800 KEM display allow you to shift between the first and second page of 18 buttons, providing access to all 36 keys.

Table 1 describes the features and benefits in more detail.

Table 1. Features and Benefits

Feature	Benefits
Illuminated Buttons	
Off (dark)	Line available
Green, steady	Line in use
Red, steady	Line in use by shared line
Amber, flashing	Line ringing
Illuminated Page Buttons	
Off (dark)	Page not in focus
Green, steady	Page in focus
Amber, flashing	Page not in focus, with one or more alerting or on-hold calls present on page
Hardware and Power-Saving Features	
Graphical display	The 4.3-inch graphical (TFT) color display provides 16-bit color depth and 480 x 272 effective pixel resolution, with backlight. The display also supports localization requiring double-byte Unicode encoding for fonts.
Articulation	You can articulate the display to match the same angle as the Cisco MP IP Phone 8851, 8861, and 8865 that it is connected to.
Directory-number and feature buttons	The module has 18 physical buttons (36 using page keys).
Page buttons	Use the two page buttons to access each page of 18 buttons and provide phone status.
Sleep or inactivity mode	When Cisco MP IP Phone 8851, 8861, and 8865 models are in power-saving sleep or inactivity mode, the Cisco IP Phone 8800 KEM is also in sleep or inactivity mode. Pressing any button on the key expansion module causes the display to awaken. The system administrator configures the inactivity period.

Cisco Multiplatform 8800 IP Phone Key Expansion Module

Product Specifications

Table 2 describes the hardware product specifications of the Cisco MP IP Phone 8800 Key Expansion Module.

Table 2. Product Specifications

Feature	Benefits
Physical dimensions (H x W x D)	9.02 x 5.15 x 1.58 in. (229.14 x 130.78 x 40.2 mm)
Weight	1.08 lb. (489g)
Power	48 VDC, 117 mA maximum
Operating temperature	32 to 104 °F (0 to 40 °C)
Relative humidity	10 to 95%
Storage temperature	12 to 140 °F (-10 to 60 °C)
Approvals and compliance	http://www.cisco.com/en/US/docs/voice_ip_comm/cuipph/all_models/regulatory_compliance/english/install/guid_e/iphrcsi3.html

System Requirements

Table 3 lists the system requirements for the 8800 KEM.

Table 3. System Requirements

Phone Firmware/Call Control Server	Release
Cisco IP Phone 8800 firmware	10.2(2) and later
Call-control compatibility	Cisco Unified Communications Manager Version 8.5(1) and later; and Cisco Unified Survivable Remote Site Telephony (SRST) 8.0 (with Cisco IOS® Software Release 15.1(1)T) and later

Cisco Multiplatform 8800 IP Phone Key Expansion Module

Power Requirements

The Cisco MP IP Phone 8800 Key Expansion Module doesn't have its own local power supply; it gets power from the attached phones. For more power-supply details, please refer to Table 4.

Table 4. Power-Supply Compatibility Table

Configuration	802.3af Power over Ethernet (PoE)	802.3at PoE	Cisco IP Phone Power Cube 4
8851 + KEM x 1	Yes	Yes	Yes
8851 + KEM x 2	No	No, (Exception - See Note Below)***	Yes
8861 + KEM x 1	No	Yes	Yes
8861 + KEM x 2	No	Yes*	Yes
8861 + KEM x 3	No	Yes*	Yes
8865 + KEM x 1	No	Yes	Yes
8865 + KEM x 2	No	Yes**	Yes
8865 + KEM x 3	No	Yes**	Yes

***Note:** The fast-charging feature on the back USB does not work when more than one KEM is attached to a Cisco MP IP Phone 8861 using 802.3at PoE.

****Note:** The fast-charging feature on the back USB doesn't work when more than one KEM is attached to a Cisco MP IP Phone 8861 unless Cisco Universal PoE (UPoE) is used.

*****Note:** 8851 with KEM x 2 will work on 802.3at PoE only with v08 or later hardware. You can find the phone version information on the lower back of the phone located within the TAN and PID label. Version information is also located on the individual phone packaging.